


## 內輪

Inner rings

MI




MI

軸徑 d		軸承型號 Series	單位重 Weight	配合軸承型號 Suitable Bearing Designaton
mm	inch	標準尺寸 Standar size 1/16 inch	g	
9.525	3/8	MI 061012	23	MR 101812
		MI 061016	30	MR 101816
12.700	1/2	MI 081212	23	MR 122012
		MI 081216	30	MR 122016
15.875	5/8	MI 101412	27	MR 142212
		MI 101416	36	MR 142216
19.050	3/4	MI 121612	32	MR 162412
		MI 121616	46	MR 162416
22.225	7/8	MI 141816	50	MR 182616
		MI 141820	59	MR 182620
25.400	1	MI 162016	59	MR 202816
		MI 162020	73	MR 202820
28.575	1 1/8	MI 182216	64	MR 223016
		MI 182220	77	MR 223020
31.750	1 1/4	MI 202416	87	MR 243316
		MI 202420	100	MR 243320

尺寸 Dimensions						
D		F		B1		r
mm	inch	mm	inch	mm	inch	min.
9.525	3/8	15.875	5/8	19.30	0.76	0.6
9.525	3/8	15.875	5/8	25.65	1.01	0.6
12.700	1/2	19.050	3/4	19.30	0.76	1
12.700	1/2	19.050	3/4	25.65	1.01	1
15.875	5/8	22.225	7/8	19.30	0.76	1
15.875	5/8	22.225	7/8	25.65	1.01	1
19.050	3/4	25.400	1	19.30	0.76	1
19.050	3/4	25.400	1	25.65	1.01	1
22.225	7/8	28.575	1 1/8	25.65	1.01	1
22.225	7/8	28.575	1 1/8	32.00	1.26	1
25.400	1	31.750	1 1/4	25.65	1.01	1
25.400	1	31.750	1 1/4	32.00	1.26	1
28.575	1 1/8	34.925	1 3/8	25.65	1.01	1
28.575	1 1/8	34.925	1 3/8	32.00	1.26	1
31.750	1 1/4	38.100	1 1/2	25.65	1.01	1.5
31.750	1 1/4	38.100	1 1/2	32.00	1.26	1.5

內輪  
Inner rings  
MI



軸徑 d		軸承型號 Series	單位重 Weight	配合軸承型號 Suitable Bearing Designaton
mm	inch	標準尺寸 Standar size 1/16 inch	g	
33.338	1 5/16	MI 212616	91	MR 263516
		MI 212620	118	MR 263520
34.925	1 3/8	MI 222816	120	MR 283716
		MI 222820	145	MR 283720
39.688	1 9/16	MI 253020	136	MR 303920
41.275	1 5/8	MI 263216	136	MR 324116
		MI 263220	173	MR 324120
44.450	1 3/4	MI 283624	286	MR 364824
		MI 283628	336	MR 364828
50.800	2	MI 324024	336	MR 405224
		MI 324028	395	MR 405228
57.150	2 1/4	MI 364424	375	MR 445624
		MI 364428	440	MR 445628
63.500	2 1/2	MI 404824	410	MR 486024
		MI 404828	480	MR 486028

尺寸 Dimensions						
D		F		B1		r
mm	inch	mm	inch	mm	inch	min.
33.338	1 5/16	41.275	1 5/8	25.65	1.01	1.5
33.338	1 5/16	41.275	1 5/8	32.00	1.26	1.5
34.925	1 3/8	44.450	1 3/4	25.65	1.01	1.5
34.925	1 3/8	44.450	1 3/4	32.00	1.26	1.5
39.688	1 9/16	47.625	1 7/8	32.00	1.26	1.5
41.275	1 5/8	50.800	2	25.65	1.01	1.5
41.275	1 5/8	50.800	2	32.00	1.26	1.5
44.450	1 3/4	57.150	2 1/4	38.35	1.51	1.5
44.450	1 3/4	57.150	2 1/4	44.70	1.76	1.5
50.800	2	63.500	2 1/2	38.35	1.51	2
50.800	2	63.500	2 1/2	44.70	1.76	2
57.150	2 1/4	69.850	2 3/4	38.35	1.51	2
57.150	2 1/4	69.850	2 3/4	44.70	1.76	2
63.500	2 1/2	76.200	3	38.35	1.51	2
63.500	2 1/2	76.200	3	44.70	1.76	2